

Uplights

E8742N Modular Recessed Uplight Green – Round – 240v GU10

Modula is a flexible range of recessed lights featuring an adjustable bracket that provides up to 30° of movement from vertical for directional lighting. Modula lights accept a range of clip on lenses and filters offering a wide choice of lighting effects



PHYSICAL DATA

The bezel is constructed from 316 grade stainless steel which is then powder coated in a green finish. The bezel is secured to the anodised aluminium tubular body via four hex bolts (key provided). The body measures 125mm long x 100mm diameter, with the bezel measuring 120mm diameter. The light is mounted in a polycarbonate sleeve measuring 175mm x 105mm diameter. The sleeve has a 2mm taper to one end. Fitted with 2m H07RN-F three core cable

ELECTRICAL DATA


240v ac – These lights must be installed by a qualified electrician. Connections should be made via suitable IP68 rated junction boxes and filled with a resin sealant post testing. Using a single RCD for large numbers of 240v fittings is not recommended due to the risk of nuisance tripping. We advise the use of separate RCD protection for each circuit and a maximum of 12 fittings per RCD

COMPATIBLE LAMPS (purchase separately)

GU10COB lamps up to 6w, GU10LED lamps up to 5w and GU10 halogen lamps up to 35w

COMPLIANCE & WARRANTY

2 Year warranty





Product Specification Sheet

Uplights

• CE / RoHS Compliant

INSTALLATION

Install the polycarbonate sleeve into the ground during construction or retrofitted into a hole cut with a coring bit: the light pushes into the tube, where it is held firmly in place by two O-rings. Suitable drainage should be provided below each fitting to prevent water logging. Connect input cable to supply via resin filled junction boxes.