



The Larkfield is a stunning IP65 rated LED Post Top with a stylish and elegant feel.

Manufactured with a beautiful aluminium louvre stack and featuring a coated black upper canopy to ensure a controlled distribution of light with minimal glare.

Options include Mini Photocell, Dali and spigot size.

Larkfield 45W - LED Post Top

Amenity Lighting



Features

- LED rating 5,880lm (4000K & 6000K).
- LED rating 4,974lm (3000K).
- Luminaire flux 5,116lm (4000K & 6000K).
- Luminaire flux 4,328lm (3000K).
- 3000K (WW), 4000K (NW) and 6000K (CW) colour temperature options.
- -20 to +40°C operating temperature.
- LED life span > 100,000hrs.
- Easy access to LED and Driver via a removable head.
- Options available include Mini Photocell, Dali and 180° Spill Shield.
- Manufactured from UV stabilised polycarbonate.
- Louvres for optimum performance and minimal upward light.
- Tamper proof fixings for increased vandal resistance.

Applications

- Car Parks
- Retail Parks
- Walk Ways
- Parks & Gardens
- Security
- Amenity Areas

www.exteriorlights.co.uk
01689 606342



Specifications

Larkfield 45W

Item Number	Description	Light Source	LED Rating (lm)	Total Wattage (W)	Colour Name	CCT(K)	CRI	Voltage	Driver Current (mA)	Luminaire Flux (lm)	Luminaire Efficacy (lm/W)	Kg	Unit Colour	Spigot Size (mm)
Standard - Black Top														
B45-A5C-00B-60	Larkfield-45W-LED-AC-6K-Std-Black-60mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Black	60
B45-A5C-00B-76	Larkfield-45W-LED-AC-6K-Std-Black-76mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Black	76
B45-A5N-00B-60	Larkfield-45W-LED-AC-4K-Std-Black-60mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Black	60
B45-A5N-00B-76	Larkfield-45W-LED-AC-4K-Std-Black-76mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Black	76
B45-A5W-00B-60	Larkfield-45W-LED-AC-3K-Std-Black-60mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Black	60
B45-A5W-00B-76	Larkfield-45W-LED-AC-3K-Std-Black-76mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Black	76
Standard - Silver Top														
B45-A5C-00S-60	Larkfield-45W-LED-AC-6K-Std-Silver-60mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Silver	60
B45-A5C-00S-76	Larkfield-45W-LED-AC-6K-Std-Silver-76mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Silver	76
B45-A5N-00S-60	Larkfield-45W-LED-AC-4K-Std-Silver-60mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Silver	60
B45-A5N-00S-76	Larkfield-45W-LED-AC-4K-Std-Silver-76mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Silver	76
B45-A5W-00S-60	Larkfield-45W-LED-AC-3K-Std-Silver-60mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Silver	60
B45-A5W-00S-76	Larkfield-45W-LED-AC-3K-Std-Silver-76mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Silver	76

Specifications

Larkfield 45W

Item Number	Description	Light Source	LED Rating (lm)	Total Wattage (W)	Colour Name	CCT(K)	CRI	Voltage	Driver Current (mA)	Luminaire Flux (lm)	Luminaire Efficacy (lm/W)	Kg	Unit Colour	Spigot Size (mm)
Standard - Black - Mini Photocell														
B45-A5C-04B-60	Larkfield-45W-LED-AC-6K-Std-M/Photocell-Black-60mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Black	60
B45-A5C-04B-76	Larkfield-45W-LED-AC-6K-Std-M/Photocell-Black-76mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Black	76
B45-A5N-04B-60	Larkfield-45W-LED-AC-4K-Std-M/Photocell-Black-60mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Black	60
B45-A5N-04B-76	Larkfield-45W-LED-AC-4K-Std-M/Photocell-Black-76mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Black	76
B45-A5W-04B-60	Larkfield-45W-LED-AC-3K-Std-M/Photocell-Black-60mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Black	60
B45-A5W-04B-76	Larkfield-45W-LED-AC-3K-Std-M/Photocell-Black-76mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Black	76
Standard - Silver Top - Mini Photocell														
B45-A5C-04S-60	Larkfield-45W-LED-AC-6K-Std-M/Photocell-Silver-60mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Silver	60
B45-A5C-04S-76	Larkfield-45W-LED-AC-6K-Std-M/Photocell-Silver-76mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Silver	76
B45-A5N-04S-60	Larkfield-45W-LED-AC-4K-Std-M/Photocell-Silver-60mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Silver	60
B45-A5N-04S-76	Larkfield-45W-LED-AC-4K-Std-M/Photocell-Silver-76mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Silver	76
B45-A5W-04S-60	Larkfield-45W-LED-AC-3K-Std-M/Photocell-Silver-60mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Silver	60
B45-A5W-04S-76	Larkfield-45W-LED-AC-3K-Std-M/Photocell-Silver-76mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Silver	76
Dali - Black Top														
B45-A5C-20B-60	Larkfield-45W-LED-AC-6K-Dali-Black-60mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Black	60
B45-A5C-20B-76	Larkfield-45W-LED-AC-6K-Dali-Black-76mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Black	76
B45-A5N-20B-60	Larkfield-45W-LED-AC-4K-Dali-Black-60mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Black	60
B45-A5N-20B-76	Larkfield-45W-LED-AC-4K-Dali-Black-76mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Black	76
B45-A5W-20B-60	Larkfield-45W-LED-AC-3K-Dali-Black-60mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Black	60
B45-A5W-20B-76	Larkfield-45W-LED-AC-3K-Dali-Black-76mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Black	76
Dali - Silver Top														
B45-A5C-20S-60	Larkfield-45W-LED-AC-6K-Dali-Silver-60mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Silver	60
B45-A5C-20S-76	Larkfield-45W-LED-AC-6K-Dali-Silver-76mm	LED	5,880	45	CW	6K	Ra>70	220-240	525	5,116	114	5	Silver	76
B45-A5N-20S-60	Larkfield-45W-LED-AC-4K-Dali-Silver-60mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Silver	60
B45-A5N-20S-76	Larkfield-45W-LED-AC-4K-Dali-Silver-76mm	LED	5,880	45	NW	4K	Ra>70	220-240	525	5,116	114	5	Silver	76
B45-A5W-20S-60	Larkfield-45W-LED-AC-3K-Dali-Silver-60mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Silver	60
B45-A5W-20S-76	Larkfield-45W-LED-AC-3K-Dali-Silver-76mm	LED	4,974	45	WW	3K	Ra>80	220-240	525	4,328	96	5	Silver	76

Legend: **M/Photocell** = Mini Photocell. **3K** = Warm White (3000K). **4K** = Neutral White (4000K). **6K** = Cool White (6000K). **WW** = Warm White. **NW** = Neutral White. **CW** = Cool White.

www.exteriorlights.co.uk

01689 606342

