



## Exterior Lights UK Ltd

The Pembury 10W is an IP65 /IK10 rated LED bollard featuring a silver optical controller to ensure minimal upward glare and a symmetrical spread for an enhanced visual experience.

Manufactured from marine grade 316 stainless steel and a transparent strong UV stabilised polycarbonate diffuser for high efficiency and vandal resistance.

Options available include bolt-on root, Dali, and 3hr Emergency.



# Pembury 10W - LED Bollard

## Bollard Lighting



## Features


- LED rating 1,320lm (4000K & 6000K).
- LED rating 1,117lm (3000K).
- Luminaire flux 1,122lm (4000K & 6000K).
- Luminaire flux 949lm (3000K).
- 3000K (WW), 4000K (NW) and 6000K (CW) colour temperature options.
- -20 to +40°C operating temperature (Emergency 0 to +40°C).
- LED life span > 100,000hrs.
- Osram LED and Osram driver.
- Easy access to LED and driver via a removable head.
- Tamper proof fixings for increased vandal resistance.
- Fused main terminal block.
- Marine Grade 316.

## Applications

- Prestigious Grounds
- Walk Ways
- Car Parks
- Security
- Parks and Gardens
- Amenity Areas

[www.exteriorlights.co.uk](http://www.exteriorlights.co.uk)

**01689 606 342**



## Specifications

### Pembury 10W

Item Number	Description	Light Source	LED Rating (lm)	Total Wattage (W)	Colour Name	CCT (K)	CRI	Voltage (VAC)	Driver Current (mA)	Luminaire Flux (lm)	Luminaire Efficacy (lm/W)	Kg	Unit Colour
<b>Standard</b>													
SB10-A1C-00-SS316	Pembury-10W-LED-AC-6K-Std-SS316	LED	1,320	10	CW	6K	Ra>70	220-240	175	1,122	112	8.25	Silver
SB10-A1N-00-SS316	Pembury-10W-LED-AC-4K-Std-SS316	LED	1,320	10	NW	4K	Ra>70	220-240	175	1,122	112	8.25	Silver
SB10-A1W-00-SS316	Pembury-10W-LED-AC-3K-Std-SS316	LED	1,117	10	WW	3K	Ra>80	220-240	175	949	95	8.25	Silver
<b>Standard - Emergency</b>													
SB10-A1C-01-SS316	Pembury-10W-LED-AC-6K-Std-E3-SS316	LED	1,320	10	CW	6K	Ra>70	220-240	175	1,122	112	9	Silver
SB10-A1N-01-SS316	Pembury-10W-LED-AC-4K-Std-E3-SS316	LED	1,320	10	NW	4K	Ra>70	220-240	175	1,122	112	9	Silver
SB10-A1W-01-SS316	Pembury-10W-LED-AC-3K-Std-E3-SS316	LED	1,117	10	WW	3K	Ra>80	220-240	175	949	95	9	Silver
<b>Dali</b>													
SB10-A1C-20-SS316	Pembury-10W-LED-AC-6K-Dali-SS316	LED	1,320	10	CW	6K	Ra>70	220-240	175	1,122	112	8.25	Silver
SB10-A1N-20-SS316	Pembury-10W-LED-AC-4K-Dali-SS316	LED	1,320	10	NW	4K	Ra>70	220-240	175	1,122	112	8.25	Silver
SB10-A1W-20-SS316	Pembury-10W-LED-AC-3K-Dali-SS316	LED	1,117	10	WW	3K	Ra>80	220-240	175	949	95	8.25	Silver

Legend: **Std** = Standard. **3K** = Warm White (3000K). **4K** = Neutral White (4000K). **6K** = Cool White (6000K). **WW** = Warm White. **NW** = Neutral White. **CW** = Cool White.