





## PATTIA-recessed fitting

LED, 3000K, square, matt black, 38°, incl. driver

The innovative PATTIA I recessed fitting is suitable for ceiling thicknesses of up to 25 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in matt black, matt white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a rigid mount, as well as the dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



## TECHNICAL DATA

|                                     |                             |
|-------------------------------------|-----------------------------|
| Item no.:                           | 114430                      |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V      |
| Secondary power / secondary voltage | 500 mA/V                    |
| Length                              | 8.0 cm                      |
| Width                               | 8.0 cm                      |
| Height                              | 4.5 cm                      |
| Installation diameter               | 6.0 cm                      |
| Installation depth                  | 6.0 cm                      |
| Net weight                          | 0.271 kg                    |
| Gross weight                        | 0.323 kg                    |
| IP Code                             | IP 20 / IP 65               |
| Safety class                        | II                          |
| Assembly                            | Recessed                    |
| Assembly details                    | Ceiling                     |
| Dimming technology                  | Leading edge, trailing edge |
| Wattage                             | 11 W                        |
| Lumen                               | 910 lm                      |
| Colour temperature                  | 3000 Kelvin                 |
| Beam angle                          | 38 °                        |
| Color                               | black                       |
| CRI                                 | >80                         |
| Binning                             | 3                           |



|                |         |
|----------------|---------|
| LXXBXX data    | 70/50   |
| Service life   | 40000 h |
| BIG WHITE Page | 409     |

**Notes**

---

---

---

---

---