


40cm, 70cm or 100cm high pole spotlights for 12v MR16 35w standard or *Powersaver* halogen lamps or l.e.d. lamps

Pole Spots feature a longer body to shield the lamp from view and provide good glare protection. Models include single or twin12v spotlight on a 40cm tubular stem - ideal for uplighting trees or taller shrubs from amongst planting, spotlighting features at ground level or washing light across a lawn or path. 30cm extension stems are available to increase the total height to 70cm or 1m, for which the E6002 High-stability Tri-Spike is recommended. Pole Spot Solo and Pole Spot Duo are weatherproof to IP66, fitted with a 1.5m rubber cable and accept an MR16 35w halogen or l.e.d. lamp. Use a Powersaver 35w lamp to provide the equivalent light output of a standard 50w halogen lamp. There is space inside the spotlight to fit a **E4010** honeycomb glare louvre or a clip-on MR16 spread lens, frosted lens or colour filter onto the lamp. Pole spotlights require T9962 cable joint kit to connect to 2.5mm low voltage cable.

Pole Spots are supplied without mount to permit selection of alternative polycarbonate spike or trispike: see next page for options. Order lamp, cable joint kit and mount separately





< E6321 Pole Spot Solo in natural copper with E6001 polycarbonate spike mount





Pole Spot Solo		
E6311	Stainless steel	
E6321	Copper	
E6331	Black	
E6371	Rustic Brown	
Pole Spot Duo		
E6411	Stainless steel	
E6421	Copper	
E6431	Black	
E6471	Rustic Brown	











HALOGEN Powersavers
12v HALOGEN LAMPS







12v twin halogen floodlight with optional extension poles for wall-washing and crosslighting

For two 20-50w halogen lamps or CAPLED I.e.d. lamp


E6271 Microflood is a 12v floodlight with 2 independently adjustable heads, providing overlapping beams ideal for uplighting hedge screens and taller shrubs or washing light across a lawn, path or gravel area. Each floodlight head can be adjusted or removed from the body for lamp replacement by twisting to release it from the twin retaining "O" rings. Microflood is weatherproof to IP66, fitted with a 1.5m rubber cable and accepts two 20w, 35w or 50w halogen capsule lamps. CAPLED3WW I.e.d. lamp is a low-energy alternative providing the equivalent of a 20w halogen capsule lamp for power consumption of 3.2w. The rustic brown powder-coated aluminium finish is inconspicuous amongst planting and in woody settings. E6002 Tri-spike 30cm high stability spike mount is recommended for use with 30cm extension poles which convert Microflood to 50cm or 80cm height amongst taller planting or for crosslighting downwards. Microflood is supplied without mount to permit selection of alternative polycarbonate spike or tri-spike: see below for options.

Use **T9962** cable joint kit for connection to 2.5mm² low voltage cable or **T9963** cable splice kit for connection to T9910 4mm² cable from a garden lighting transformer. Use T9910 4mm² cable for longer runs or for use with twin 50w lamps.

Order lamps, cable joint/splice kit, extension poles & mount separately




< Wall-washing with Microflood twin halogen floodlight using two 35w lamps makes a feature of this wisteriaclad wall




Energy Rating

A CAPLED L.E.D. LAMP

12v HALOGEN LAMP









Above: 30cm extension pole

< E6002 Tri-spike

30cm high-stability spike mount for loose soils and tall lights. Black powder-coated stainless steel

E6001 polycarbonate spike-mount >



Microflood & Pole Spot spike-mounts & accessories

E4010	58mm honeycomb glare louvre		
E6001	Black polycarbonate mounting spike		
E6002	Tri-spike high stability ground spike		
E6011	30cm pole extension	Stainless steel	
E6021	30cm pole extension	Natural copper	
E6031	30cm pole extension	Black	
E6071	30cm pole extension	Rustic brown	