




KAMUELA

fire protection recessed ceiling light, LED, 3000K, black, 38°, dimmable, IP65

The KAMUELA ECO LED recessed fitting is equipped with an integrated premium LED. The recessed light is made of aluminium and plastic and is fitted with a warm-white LED. The fire-resistant recessed fitting series is fire-resistant for at least 90 minutes. An appropriate dimmable constant current driver is integrated for operating the recessed fitting, and is therefore suitable for direct connection to 230 Volts. This luminaire contains built-in LED lamps and is available with different housing colours.



TECHNICAL DATA

Item no.:	1001015
Lamps included	0
Primary nominal voltage	220-240V ~50Hz mA/V
Height	7.1 cm
Diameter	8.8 cm
Installation diameter	7.0 cm
Installation depth	7.1 cm
Net weight	0.272 kg
Gross weight	0.319 kg
IP Code	IP 65
Safety class	II
Impact resistance class	IK02
Impact resistance	0,200000000000000001 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimming technology	Leading edge
Wattage	6.5 W
Lumen	400 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black
CRI	>80



Binning	6
LXXBXX data	70/50
Service life	25000 h
BIG WHITE Page	404

Notes
