



PATTA-I

LED outdoor recessed ceiling light, round DL IP65 white 1800-3000K

The innovative PATTA I recessed fitting is suitable for ceiling thicknesses of up to 20 mm. Rated IP65 it can be used outdoors or in damp areas. The light is available in black, white, or silver-grey, and with a round or square shape. The light colour can be individually adapted thanks to the use of a powerful, Dim to Warm LED. The electrical connection is made directly to the 230V mains supply thanks to the built-in LED driver.

TECHNICAL DATA

Item no.:	1002099		
Primary nominal voltage	220-240V ~50/60Hz mA/V		
Secondary power / secondary voltage	350 mA/V		
Height	4.0 cm		
Diameter	8.0 cm		
Installation diameter	6.0 cm		
Installation depth	6.0 cm		
Net weight	0.229 kg		
Gross weight	0.299 kg		
IP Code	IP 20 / IP 65		
Safety class	II		
Impact resistance class	IK02		
impact resistance class	INUZ		
Impact resistance	0,20000000000000001 Joule		
Impact resistance	0,20000000000000001 Joule		
Impact resistance Assembly	0,20000000000000001 Joule Recessed		
Impact resistance Assembly Assembly details	0,20000000000000001 Joule Recessed Ceiling		
Impact resistance Assembly Assembly details Dimmable	0,20000000000000001 Joule Recessed Ceiling Ja		
Impact resistance Assembly Assembly details Dimmable Dimming technology	0,2000000000000001 Joule Recessed Ceiling Ja Dim-to-Warm		
Impact resistance Assembly Assembly details Dimmable Dimming technology Wattage	0,20000000000000001 Joule Recessed Ceiling Ja Dim-to-Warm 7.3 W		
Impact resistance Assembly Assembly details Dimmable Dimming technology Wattage Lumen	0,200000000000000000000000000000000000		
Impact resistance Assembly Assembly details Dimmable Dimming technology Wattage Lumen Beam angle	0,20000000000000001 Joule Recessed Ceiling Ja Dim-to-Warm 7.3 W 440 lm 38 °		





Binning	3
LXXBXX data	70/50
Service life	30000 h
BIG WHITE Page	466

Notes			