




## OUT 65

**outdoor recessed ceiling light, LED, 3000K, round, black, 38°, 12W, incl. driver**

The innovative OUT 65 recessed ceiling light captivates with its exceptional looks. Rated IP65 it can be used outdoors or in damp areas. It is available in black, white, silver-grey or titanium, and in round or square form. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.

## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 114460                 |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500 mA/V               |
| Height                              | 6.0 cm                 |
| Diameter                            | 8.5 cm                 |
| Installation diameter               | 7.0 cm                 |
| Installation depth                  | 6.0 cm                 |
| Net weight                          | 0.319 kg               |
| Gross weight                        | 0.393 kg               |
| IP Code                             | IP 20 / IP 65          |
| Safety class                        | II                     |
| Assembly                            | Recessed               |
| Assembly details                    | Ceiling                |
| Wattage                             | 11.0 W                 |
| Lumen                               | 510 lm                 |
| Colour temperature                  | 3000 Kelvin            |
| Beam angle                          | 38 °                   |
| Color                               | black                  |
| CRI                                 | >80                    |
| Binning                             | 3                      |
| LXXBXX data                         | 70/50                  |
| Service life                        | 40000 h                |





|                |     |
|----------------|-----|
| BIG WHITE Page | 708 |
|----------------|-----|

**Notes**

---

---

---

---

---