


## FLATT POLE 100

## Outdoor LED floor stand, 3000K, IP65, anthracite/brown

Would you like a floor stand which can be effortlessly mounted on the floor? This should have a safety class of at least IP 65, and therefore be thus dustproof and protected from water spray from various directions. Our FLATT POLE 100 has IP 65 and is therefore brilliant for lighting a path or the terrace. Are you looking for amazing light for your outdoor area? This is provided by the built-in Premium LED of the FLATT POLE 100 floor stand. Incidentally, the FLATT POLE 65 gives you even more advantages as a part of the SLV family. Because we have been successful with our lighting concepts for 40 years, and keep setting the bar higher for ourselves and our products.



## **TECHNICAL DATA**

| Item no.:                           | 1002959                     |
|-------------------------------------|-----------------------------|
| Primary nominal voltage             | 100-240V ~50/60Hz mA/V      |
| Secondary power / secondary voltage | 350 mA/V                    |
| Length                              | 18.0 cm                     |
| Width                               | 4.5 cm                      |
| Height                              | 100.0 cm                    |
| Net weight                          | 4.47 kg                     |
| Gross weight                        | 4.783 kg                    |
| IP Code                             | IP 65                       |
| Safety class                        | 1                           |
| Impact resistance class             | ІКОЗ                        |
| Impact resistance                   | 0,3499999999999999998 Joule |
| Assembly                            | Surface                     |
| Assembly details                    | Ground                      |
| Wattage                             | 9.7 W                       |
| Lumen                               | 400 lm                      |
| CRI                                 | >80                         |
| Binning                             | 6                           |
| Service life                        | 54000 h                     |
| Ambient temperature                 | 40 °C                       |
| Minimum ambient temperature         | -25 °C                      |
| Maximum ambient temperature         | 40 °C                       |
|                                     |                             |



**BIG WHITE Page** 

569

## Accessories

228730 CONNECTION BOX , 3-pin, IP68

Notes