

Product Specification Sheet

MR16 GU5.3 8.3W (51W) 4000K 700lm Dimmable

Partcode: ILMR16DE040 / Page: 1



The Integral LED Classic MR16 range offers a fantastic ratio of value and performance. By incorporating a stylish engineered lens in an affordable spotlight, the Classic offers directional light with a beam angle that closely mirrors that of familiar halogen lamps along with all the energy-saving and long-life benefits of LED.

Product Details

Partcode: ILMR16DE040

Check Code: 304205 Range Name: Classic

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: MR16 Warranty: 2 Years CE / RoHS: Yes

Physical Data

Base Type: GU5.3

Base Colour: Matt white Product Finish: Matt white

Spot Type: SMD with "COB like effect"
Optic: Designed to give a Classic Look

Material: Plastic and Aluminium heat-sink, Injection moulded diffuser

Construction: Plastic White and "Classic look" diffuser lens



Product Specification Sheet

Partcode: ILMR16DE040 / Page: 2

Physical Data

Length: 45mm Diameter: 50mm

Weight (Unpackaged Single Unit): 45g

Lamp or Luminaire Shape: Round

Lamp Fixing: Downlight

Electrical Data

Voltage Range: 12V

Power Consumption: 8.3 Watts

Driver included: No, needs 12V AC Transformer

Driver IC Manufacturer: Silergy

Electric Current: AC Ampage: 700.00mA

Frequency Range: 50 Hz Power Factor: >=0.90

Wattage Equivalent: 51 Watts

Dimming: Dimmable with compatible dimmers

LVD Certified: Yes EN: EN-62560

Light Data

Useful Lumens: 640lm (Rated luminous flux in a 90° cone)

Lumens: 700lm

Lumens per Watt: 84.0lm/W Peak Intensity: 1,600Cd

Beam Angle: 36°

Correlated Colour Temperature (CCT): 4000k

Colour Temperature: Cool White
Colour Rendering Index (CRI): >=80

LED Type: Surface mounted device (SMD)

LED Size: 2835

Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs


Switching Cycles: >7,500 X



Product Specification Sheet

Partcode: ILMR16DE040 / Page: 3

Environmental



Energy Rating: A+

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP20

Hg 0% (Mercury Free): Yes

Packaging

EAN Barcode (unit of 1): 5055788230816

Packaged Weight (Unit of 1): 65g

Length (unit of 1): 60mm Width (unit of 1): 55mm Depth (unit of 1): 55mm

Outer packaging info available on website

Product data last updated on: Tuesday, January 7, 2020 - 10:50