Path, Step & Deck

E1142TL Cirrus 45 Bollard Light with louvres- Teak

Elipta Teak bollard lights use timber from a sustainable source, organically oiled during production to enhance and protect the grain. They will weather naturally in the garden; further oil, stain or varnish treatments may be applied by the user. Teak bollard lights may be bolted to paving and slabs or to an optional groundmount which can be installed in concrete prior to electrical installation. An optional galvanised ground spike is available for installation in planting and lawn areas.



PHYSICAL DATA

- Height 450mm
- Width 100mm (top) 136mm (base) square

ELECTRICAL DATA


- 220 240v AC
- E27 lamp fitting

COMPATIBLE LAMPS (purchase separately)

- E27 LED candle lamp 7-watt
- E27 Compact fluorescent 20-watt max

INSTALLATION

Pre-wired with 2m rubber cable for connection via T9969 underground joint kit or T9961 3 pole IP68 inline connector. Using a single RCD for large numbers of 240v fittings is not recommended due to the risk of nuisance tripping. We advise the use of separate RCD protection for each circuit and a maximum of 12 fittings per RCD.



COMPLIANCE & WARRANTY

- 2 year warranty
- CE / RoHS Compliant

Exterior Lights UK Ltd Registered No.8249488

Registered Office: P.O. Box 794, Orpington, Kent. BR6 1FB

Web: www.exteriorlightsuk.co.uk Email: sales@exteriorlightsuk.co.uk