

Thank you for purchasing this light fitting. Please read the instructions carefully before use to ensure safe and satisfactory operation of this product. Please retain these instructions for future reference.

Varning

Please read these instructions carefully before commencing any work.

This unit must be fitted by a competent and qualified electrician.

Install in accordance with IEE Wiring regulations and current Building Regulations.

Check the pack and make sure you have all of the parts listed.

To prevent electrocution switch off at mains supply before installing or maintaining this fitting.

Ensure other persons cannot restore the electrical supply without your knowledge.

This light fitting should be connected to a circuit with a 30mA RCD fitted.

If replacing an existing fitting, make a careful note of the connections.

This product is manufactured from marine grade stainless steel, making it suitable for application in coastal environments.

This bricklight product is specifically designed and tested for installation into vertical walls only. Under no circumstances should it be fitted into the ground or into horizontal surfaces.

This product is not suitable for dimming.

Waste electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your local authority or retailer for recycling advice.

Technical data

Supply Voltage:	240V~, 50 Hz
Bulb Type:	LED (3.5W) 2835 SMD module 4000K - 200lm (78637/78638) LED (3.5W) 2835 SMD module 3000K - 200lm (78636/78640) LED (3.5W) 2835 SMD module 3000K - 200lm (78641)
	The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.
	Conformity with all relevant EC Directive requirements.
	Waste electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your Local Authority or local store for recycling advice.
	The power supply is Double Insulated and does not require connection to an Earth circuit.
	This product is not suitable for dimming.
IP44	Splash-proof

Installation

- Existing fittings must be completely removed before installation of a new product. Before removing the existing fitting, carefully note the position of each set of wires.
- N.B.: for 78637/78638 there is an additional interchangeable Warm White LED module that, if desired, can be purchased separately. The reference number is 78641. Using the supplied hex key, remove the front panel by unscrewing the two hexagonal screws. Then disassemble the bricklight; LED module can be replaced with 78641.
 - Select a mounting location for the product and prepare a cut out size of H65mm x W215mm x D102.5mm. If removing an existing brick, the mortar should not be removed.
 - Pass the incoming supply cable through the cut out and through the outer frame.
 - Fit the 4 spring clips into the outer frame by pushing them into the slots. Ensure they are securely fitted and then securely fit the outer frame into the wall. See Fig 2.
 - Avoid locating any cables in positions that would cause a hazard. Position cables and outdoor rated junction boxes (not supplied) away from areas where they may be at risk from being cut, trapped or damaged.
 - Which is an outdoor grade, rubber sheathed cable. The mains supply cable must have a minimum cross sectional area of 1.0mm²
 - Cables must be protected using suitable conduit or plastic trunking.
 - Product must only be installed into vertical walls.
 - Tighten the cable gland to ensure waterproof seal.
 - Re-assemble the bricklight, ensuring the front bezel is securely fitted to ensure waterproof seal.
 - Switch on. Your light is now ready for use.

